

PERRY JOHNSON LABORATORY ACCREDITATION, INC.

Certificate of Accreditation

Perry Johnson Laboratory Accreditation, Inc. has assessed the Laboratory of:

DRL & Asociados, S.R.L.

Plaza ABBA, Avenida de Los Proceres No. 20, Urbanización Las Avenidas Santo Domingo DN, República Dominicana. C.P. 10601

(Hereinafter called the Organization) and hereby declares that Organization is accredited in accordance with the recognized International Standard:

ISO/IEC 17025:2017

This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (as outlined by the joint ISO-ILAC-IAF Communiqué dated April 2017):

Mechanical Testing (As detailed in the supplement)

Accreditation claims for such testing and/or calibration services shall only be made from addresses referenced within this certificate. This Accreditation is granted subject to the system rules governing the Accreditation referred to above, and the Organization hereby covenants with the Accreditation body's duty to observe and comply with the said rules.

For PJLA:

Tracy Szerszen President

Perry Johnson Laboratory Accreditation, Inc. (PJLA) 755 W. Big Beaver, Suite 1325 Troy, Michigan 48084 Initial Accreditation Date: Issue Date: June 21, 2023 June 21, 2023 Accreditation No.: C 109973

Certificate No.: L23-484

Expiration Date:

September 30, 2025

The validity of this certificate is maintained through ongoing assessments based on a continuous accreditation cycle. The validity of this certificate should be confirmed through the PJLA website: <u>www.pjlabs.com</u>



Certificate of Accreditation: Supplement

DRL & Asociados, S.R.L.

Plaza ABBA, Avenida de Los Proceres No. 20, Urbanización Las Avenidas Santo Domingo DN, Republica Dominicana. C.P. 10601 Contact Name: Walter de la Rosa Phone: 809-216-3938

Accreditation is granted to the facility to perform the following testing:

FIELD OF TEST	ITEMS, MATERIALS OR PRODUCTS TESTED	SPECIFIC TESTS OR PROPERTIES MEASURED	SPECIFICATION, STANDARD METHOD OR TECHNIQUE USED	RANGE (WHERE APPROPRIATE) AND DETECTION LIMIT
Mechanical	Biosafety	Design Qualification	Costumer	0.3 μm to 10 μm
Testing ^O	Cabinets Clean	Installation	Requirement	0.36 m/s to 0.54 m/s
	Rooms (Particle	Qualification	ISO 14644	18 °C to 25 °C
	Counts, Airflow	Operating	DPD	30 % RH to 75 % RH
	Volume and	Qualification.	Air Hood and Air	Up to 10 Pa
	Master,	Performance	Meter,	100 Lux to 2 000 Lux
	Temperature,	Qualification	Digital	Visual
	Humidity		Thermohigrometer,	0.003 %, 0.005 %
	Differential		Manometer	
	Pressure,		Lux Meter	
	Lux Meter,		Smoke Candles	
	Flow		DPD	
	Visualization and			
	Integrity)			
	Fume Hood		Costumer	0.36 m/s to 0.54 m/s
	(Airflow Master,		Requirement	Up to 10 Pa
	Differential		ASHRAE D-86331	Visual
	Pressure,		Air Meter,	100 Lux to 2 000 Lux
	Flow		Manometer	
	Visualization		Smoke Candles	
	Lux Meter)		Lux Meter	
	Metal Detector,	Particle sizes	ASTM 7046	0.01 mm to 10 mm
	Ferrous,		Costumer	Detect/ Non-Detect
	Non-Ferrous,		Requirement	
	Stainless Steel			

1. The presence of a superscript O means that the laboratory performs testing of the indicated parameter onsite at customer locations. Example: Outside Micrometer^O would mean that the laboratory performs this testing onsite at the customer's location.